

- Best suction capacity and excellent sweeping performance in its class
- Less maintenance and cost of ownership
- Easy to handle and comfortable cabin to hassle free operation
- Wide range of optional equipment and attachment such as third brush, snow brush, snow blades, rear wander hose, high-pressure water pump



Experienced Performance

SICI AGA 2100

HYDROSTATIC COMPACT SWEEPER



Distributor Information

Sici Srl
Address: Via Roma, 30 - 37029 San Pietro in Cariano (VR) - Italy
Phone: +39 328 7180933
 info@sicisrl.it - www.sicisrl.it

SICI AGA 2100

HYDROSTATIC COMPACT SWEEPER



CAPACITY INFORMATION

| | |
|---------------------|--------------------|
| Hopper volume | 2 m ³ |
| Payload volume | 1.5 m ³ |
| Payload capacity | 1 ton |
| Water tank | 300 lt. |
| Hydraulic reservoir | 130 lt. |

ENGINE INFORMATION

| | |
|--------------------|---|
| Brand - Model | 3.9 lt. 4 Cylinder Water cooled Tumosan Diesel Engine |
| Power | 85 hp / 63 kW @ 2.300 RPM |
| Torque | 330 Nm @ 1.500 RPM |
| Emission | EPA Tier 3 and EU Stage 3A |
| Fuel tank capacity | 65 lt. |

SWEEPING EQUIPMENTS

| | |
|-------------------------------------|---|
| Brush diameter | Ø 400 mm - 0 - 150 RPM Hydraulic motor driven |
| Suction hose diameter | Ø 200 mm |
| Suction nozzle width | 650 x 400 mm |
| Sweeping width | 1.500 mm |
| Sweeping speed | Up to 15 km / h |
| Sweeping capacity | Up to 22.500 m ² |
| Cruising speed | 25 km / h |
| Variable and adjustable brush speed | |

GENERAL INFORMATION

| | |
|----------------------|--|
| Tire size | 6.5 L 10 |
| Wheelbase | 1.430 mm |
| Dump height | 1.600 mm |
| Dump angle | 50° ± 5° |
| Filter mesh area | 0,5 m ² |
| Hydraulic filtration | 100 micron suction / 20 micron return |
| Gradeability | %25 |
| Brake | Hydraulic type front and rear dynamic brake system |
| Hopper construction | Stainless steel |

Able to dump to garbage compactor tailgate and 1.100 lt garbage container directly

FAN

| | |
|-----------------------|--|
| Type | Heavy duty, dynamically balanced impeller with multivane corrosion resistance blades |
| Operation speed | 3.500 RPM |
| Flow rate | 8.250 m ³ / h |
| Construction material | Stainless steel AISI304 |

CABIN - CONTROL PANEL

| |
|---|
| Adjustable and telescopic hydraulic steering wheel |
| Single seat ergonomic cabin |
| In cabin climate control with air condition |
| Tilttable cabin for easy service access |
| Radio and CD player |
| Display screen |
| Engine RPM display |
| Raised hopper warning |
| Auxiliary engine hour gauge |
| Water level indicator |
| Fuel indicator |
| Camera system with in cabin 7" screen, rear view and suction nozzle cameras |

OPTIONS

| |
|--|
| Rear wander hose |
| Snow blade |
| Snow sweeping brush |
| Third brush |
| 16 lt. / 100 bar water pump with high pressure washing gun |